



usimeca
WWW.USIMECA.COM.BR

BRUTUS

• REAR LOADER

	Brutus 18	Brutus 20	Brutus 25	Brutus 28
DIMENSIONS				
Body Capacity	13,9 m3 (18,1 yd3)	15,4 m3 (20,1 yd3)	19,2 m3 (25,1 yd3)	21,1 m3 (27,6 yd3)
Hopper Capacity	2,2 m3 (3,0 yd3)			
Total Capacity	16,1 m3 (21,1 yd3)	17,6 m3 (23,1 yd3)	21,4 m3 (28,1 yd3)	23,3 m3 (30,6 yd3)
Base Line (1)	3,43 m (135")	3,75 (148")	4,55 m (179")	4,93 m (194")
Overall Length	5,03 m (198")	5,34 m (210")	6,15 m (242")	6,53 m (257")
Height Above Chassis Frame	2,42 m (95")			
Overall Width	2,44 m (96")			
Hopper Width	2,08 m (82")			
Hopper Bottom Bellow Chassis Frame	514 mm (20")			
WEIGHTS				
Approx. Body Weight (STD version)	5.270 kg (11.610 lbs)	5.380 kg (11.850 lbs)	5.740 kg (12.640 lbs)	5.890 kg (12.980 lbs)
Approx. Body Weight (HD version)	5.530 kg (12.180 lbs)	5.640 kg (14.420 lbs)	6.020 kg (13.260 lbs)	6.160 kg (13.570 lbs)
CHASSIS				
Type	4 x 2		6 x 2 (3) ou 6 x 4	
Min. GVWR Requirement (2)	16,0 t (35.000 lbs)		23,0 t (50.660 lbs)	
HYDRAULICS				
Operating Pressure	150 bar (2.175 PSI)			
Packing Cycle Time	22 - 24 segundos			
Discharge Cycle Time	20 - 22 segundos			
ACCESSORIES				
Safety	Steps and Grabs handles for 3 to 4 operators			
Lighting	According with transit standards			
Communication	Buzzer system enable loader to signal the driver			
Miscellaneous	Shovel and broom support			
OPTIONALS				
Heavy Duty (HD) version	steel, compaction panels and hydraulic for heavy duty			
Sump Tank	100 liters			
Lighting	Strobe light / Hopper Lighting / Wire Mesh Protection			
Packing System	Automatic compaction cycle with electronic logic			
Container Handling Systems	roll bar / winch / cart and litter lifter			
Others	upon request			

- Notes: (1) The base line must be usable with no obstructions protruding above frame
 (2) The GVWR of the truck selected must be capable of carrying net weight of refuse to be collected
 (3) Specifications may be changed without notice and without obligation to install them on units sold.
 (4) Illustrations shown may include optional equipments and may not include all standard equipment.