

## GTJZ0608S

- Imported battery offers 8 hours run time under normal conditions
- Highly stable - can operate on 3 degree longitudinal and 1.5 degree lateral slope
- Super low maintenance self-lubricating bearings in some components
- Platform can be dismantled for transportation



## Technical Parameters

### Technical Parameters

Model	GTJZ0608S
<b>Productivity</b>	
Max. Platform height	5.8M
Max. Working height	7.8M
Extension outreach	0.9M
Turning radius (outside)	1.49M
Turning radius (inside)	0M
Rising/Falling speed (Without loading)	15~20s/25~30s
Grade ability	25%
Load capacity (Platform)	230kg
Driving Speed(stowed)	0~3km/h
Driving Speed (raised)	0~0.8km/h
Max allowable slope (front/back)	3°
Max allowable slope (side/side)	1.5°
Max. Platform Occupants(Indoor)	2
Max. Allowable Side Force(Indoor)	400N
<b>Dimensions</b>	
Overall length(stowed)	1.78M
Overall width(stowed)	0.76M
Overall height (stowed, Guardrail unfolded)	1.86M
Overall length(stowed, Guardrail folded)	2.12M
Overall height (stowed, Guardrail folded)	2.12M
Ground clearance	0.07M
Wheelbase	1.325M
Platform Size (L*W*H)	1.64*0.76*1.1M
Overall weight	1526kg
Tire	305*115 MM/solid
Hydraulic oil tank vol.	15L
Battery Voltage/Capacity	6V*4/225AH
Control Voltage	24VDC
Power Unit	24VDC, 3KW
Drive & steer model	2WD, front wheel
Input voltage of Charger	100~240V AC
Output current of Charger	25A
Hydraulic system pressure	24MPA
Brake	2 rear wheel

