

GTJZ1212

- Imported battery offers 8 hours run time under normal conditions
- Highly stable - can operate on 3 degree longitudinal and 1.5 degree lateral slope
- Super low maintenance self-lubricating bearings in some components
- Platform can be dismantled for transportation



Technical Parameters

Technical Parameters

Model	GTJZ1212
Productivity	
Max. Platform height	11.9M
Max. Working height	13.9M
Extension outreach	0.9M
Turning radius (outside)	2.35M
Turning radius (inside)	0M
Rising/Falling speed (Without loading)	63~68s/44~49s
Grade ability	25%
Load capacity (Platform)	320kg
Driving Speed(stowed)	0~3.2km/h
Driving Speed (raised)	0~0.8km/h
Max allowable wind speed	12.5m/s
Max allowable slope (front/back)	3°
Max allowable slope (side/side)	1.5°
Max. Platform Occupants(Indoor)	2
Max. Platform Occupants(Outdoor)	1
Max. Allowable Side Force(Indoor)	400N
Max. Allowable Side Force(Outdoor)	200N
Dimensions	
Overall length(stowed)	2.39M
Overall width(stowed)	1.15M
Overall height (stowed, Guardrail folded)	1.98M
Overall height (stowed, Guardrail unfolded)	2.6M
Ground clearance	0.1M
Wheelbase	1.85M
Platform Size (L*W*H)	2.25*1.15*1.1M
Overall weight(for indoor and outdoor use)	2900kg
Overall weight(indoor use only)	2615kg
Tire	380*125 MM/solid
Hydraulic oil tank vol.	35L
Battery	6V*4/260AH
Control Voltage	24VDC

