

## GTZZ15

- Compact design with zero tails wing for excellent operating efficiency in narrow spaces.
- Powerful lift and excellent lift capacity, adaptable to smooth and rough terrain.
- Computer automatically detects and determines safe working range, ensuring operator safety.



## Technical Parameters

### GTZZ15 parameters

Item	Measurement	Item	Measurement
<b>Dimensions</b>		<b>Productivity</b>	
Overall length(stowed)	5.6M	Platform height max.	14.8M
Overall width(stowed)	2.26M	Working height max.	16.8M
Overall height(stowed)	2.22M	Horizontal reach max.	7.62M
Ground clearance	0.32M	Turntable rotation	355°
Wheelbase	2.03M	Platform rotation	160°
Overall weight	7300kg (4WD)	Platform Load capacity	250kg
Platform Size (L*W*H)	1.83*0.85*1.1M	Grade ability	40% (4WD)
Platform leveling	Automatic	Turning radius(outside)	4.5M
Tire specification	33x12-20	Turning radius(inside)	1.8 M
Tire type	Solid	Turntable tails wing	0M
<b>Power</b>		Max. Driving Speed	7km/h
Hydraulic tank vol.	112l	Driving Speed (stowed)	0~7km/h
Fuel tank vol.	70L	Driving Speed (extended)	0~1.1km/h
Control voltage	12VDC	Max allowable wind force	12.5m/s
Engine	Perkins	Max allowable slope	3°
Drive & steer model	4WD*2WS	Max allowable side force	400N



## II.

**Optional:** (All “option” configure will be charged per quotation)

- Working light
- Foam tire
- Platform AC power
- Anti-collision device

