

GTZZ16EJ

- Strong loading capacity of 230kg combined with great grade-ability at 40%
- Large operational range at max horizontal extension of 9.37m and max operational height of 17.8 m, large operational range
- Electric drive is energy saving and noise reducing, making for a high efficiency, environmentally friendly product



Technical Parameters

GTZZ16EJ Parameters

Item	Measurement
Product Performance	
Platform height max.	15.7M
Working height max.	17.7M
Horizontal reach max.	9.3M
Turntable rotation	365°
Platform rotation	160°
Platform load capacity	230kg
Grade ability	30% (2WD)
Turning radius(outside)	3.31M
Turning radius(inside)	0.7M
Turntable tailswing	50mm
Driving Speed (stowed)	0~5.2km/h
Driving Speed (extended)	0-0.8km/h
Max allowable wind force	12.5m/s
Max allowable slope	5°
Max allowable side force	400N
Product Dimension	
Overall length(stowed)	6.8m
Overall width(stowed)	1.9m
Overall height(stowed)	2.0m
Ground clearance	0.22m
Wheelbase	1.9m
Platform Size (L*W*H)	1.45m*0.85m*1.1m



Overall weight	7300kg
Tire specification	250*15/solid
Control Voltage	12VDC

II.

Optional configurations and devices:

1. AC power outlets;
2. Charging cable apply to socket standards from different countries.
3. non-marking solid tyre

Remark: For the items which will cost extra, please refer to the commercial quotation related.

