

GTZZ25J

- Strong loading capacity with a max loading capacity of 230kg
- Wide working range with a max horizontal reach of 16.1m
- Excellent grade ability at 45% for 4WD
- Generous max driving speed of 4.8 km/h.



Technical Parameters

GTZZ25J parameters

Item	Measurement
Productivity	
Max. Platform height	24.6M
Max. Working height	26.6M
Max. Horizontal reach	16.1M
Turning radius(inside/outside)	3.00M /6.33M
Turntable tail swing	1M
Turntable rotation	360°continuous
Platform rotation	160°
Grade ability	45% (4WD)
Platform Load capacity	230kg
Driving Speed (stowed)	0~4.4km/h
Driving Speed (extended)	0~1.1km/h
Max allowable wind speed	12.5m/s
Max allowable slope	5°
Max noise on normal use	82dB(A)
Max allowable side force	400N
Dimensions	
Overall length(stowed)	11.51M
Overall width(stowed)	2.49M
Overall height(stowed)	3.2M
Ground clearance	0.39M
Wheelbase	3.05M
Platform Size (L*W*H)	2.44*0.91*1.1M
Overall weight	16300kg (4WD)
Tire specification	385/65-24/10Solid
Hydraulic oil tank vol.	170L
Hydraulic system vol.	28MPa
Fuel tank vol.	160L
Control voltage	12VDC
Engine	Cummins/Deutz
Drive & steer model	4WD*2WS



II.

Optional: (All “option” configure will be charged per quotation)

- Working light
- Foam tire
- Platform AC power
- Anti-collision device

